

MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier : VALVE-MEDIC

Product Use : Engine oil additive for cleaning valves.

Chemical Family : Mixture.

Manufacturer part no. : M3712C

Supplier's name and address:

Radiator Specialty Co., of Canada

1711 Aimco Blvd.
Mississauga, ON, Canada
L4W 1H7

Manufacturer's name and address:

Refer to Supplier

Information Telephone # : (905) 625-9117 (Monday - Friday, 8AM - 4PM)

24 Hr. Emergency Tel # : 613-996-6666 (CANUTEC)

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR).

WHMIS classification:

Class B3 (Combustible Liquids);

Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material);

Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

Labelling: Phrases recommended to appear on a supplier label, can be found in Section 15.

WHMIS symbols required on a supplier label:



Emergency Overview

: Black liquid. Petroleum odour.
WARNING! Combustible liquid and vapour. Harmful if inhaled. Harmful or fatal if swallowed. May be harmful if absorbed through the skin. May cause respiratory irritation. May cause nausea, vomiting, headache and other central nervous system effects. May be an aspiration hazard. Can enter the lungs and cause damage. May cause skin irritation. Contains material which can cause damage to the blood system, the liver and the kidneys. Contains material which may cause cancer, based on animal data. Possible birth defect hazard - contains material that may cause birth defects, based on animal data.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation : May cause irritation to the nose, throat and upper respiratory tract. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.

Skin : May cause mild to moderate irritation. Prolonged contact, such as when trapped against the skin under clothing or jewelry, may be more irritating. May be absorbed and cause symptoms similar to those for inhalation.

Eyes : May cause mild eye irritation. Symptoms may include stinging and tearing.

Ingestion : May cause irritation of mouth, throat, and stomach. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Material is an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Effects of long-term (chronic) exposure

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Repeated overexposure to naphthalene may cause destruction of red blood cells with anemia, fever, jaundice and kidney and liver damage. Prolonged or repeated inhalation of mists may cause coughing, increased mucous formation and difficulty breathing.

Carcinogenic status : Possible cancer hazard. See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : May cause birth defects. See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: Contains material that may be harmful in the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>Wt.%</u>
Petroleum distillates	68476-34-6	85.00 - 95.00
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	7.00 - 13.00
Solvent refined heavy paraffinic distillate	64741-88-4	0.10 - 1.00
Naphthalene	91-20-3	0.10 - 1.00
Xylene	1330-20-7	0.10 - 1.00

SECTION 4 - FIRST AID MEASURES

- Inhalation** : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention.
- Skin contact** : Remove/Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. If irritation persists, seek prompt medical attention.
- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, seek prompt medical attention.
- Ingestion** : Seek immediate medical attention/advice. Do not induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Notes For Physician** : Treat symptomatically. This product is a CNS depressant.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

- : Combustible liquid and vapour. Will ignite when exposed to heat, flame and other sources of ignition. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Vapours may be heavier than air and may collect in confined and low-lying areas. Material will float on water and can be re-ignited at the water's surface.

Oxidizing properties : None known.

Explosion data: Sensitivity to mechanical impact / static discharge

- : Not expected to be sensitive to mechanical impact. May be sensitive to static discharge.

Suitable extinguishing media : Dry chemical, foam, carbon dioxide and water fog. Do not use water jet, as this may spread burning material.

Special fire-fighting procedures/equipment

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

Hazardous combustion products

- : Carbon oxides; Nitrogen oxides (NOx); Sulphur oxides; Phosphorus compounds; Aldehydes; Hydrocarbons; Polycyclic aromatic hydrocarbons; Other unidentified organic compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up.

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Spill response/cleanup : Ventilate area of release. Remove all sources of ignition. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.

Prohibited materials : Do not use combustible absorbents, such as sawdust.

SECTION 7 - HANDLING AND STORAGE

Safe Handling procedures : Use in a well-ventilated area. Wear suitable protective equipment during handling. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Use proper bonding and grounding techniques when transferring liquid. Avoid contact with incompatible materials. Wash thoroughly after handling. Keep containers closed when not in use.

Storage requirements : Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials : Acids; Strong oxidizing agents; Alkalies.

Special packaging materials : Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits

<u>Ingredients</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Petroleum distillates	100 mg/m ³ (vapor and aerosol, as total hydrocarbons) (skin)	N/Av	N/Av	N/Av
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m ³ (inhalable) (As 'Oil mist, mineral')	N/Av	5 mg/m ³ (As 'Oil mist, mineral')	N/Av
Solvent refined heavy paraffinic distillate	5 mg/m ³ (inhalable) (As 'Oil mist, mineral')	N/Av	5 mg/m ³ (As 'Oil mist, mineral')	N/Av
Naphthalene	10 ppm (skin)	N/Av	10 ppm	N/Av
Xylene	100 ppm	150 ppm	100 ppm	N/Av

Ventilation and engineering measures

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection : If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists.

Skin protection : Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers.

Eye / face protection : Safety glasses with side-shields or chemical splash goggles.

Other protective equipment : Wear resistant clothing and boots. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

: Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink, smoke or use cosmetics while working with this product. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquid.	Appearance	: Black liquid.
Odour	: Petroleum odour.	Odour threshold	: N/Av
pH	: N/Av		
Boiling point	: 115.6°C (240°F)	Specific gravity	: 0.86
Melting/Freezing point	: N/Av	Coefficient of water/oil distribution	: N/Av

Vapour pressure (mmHg @ 20° C / 68° F)	: Insoluble.
: N/Av	
Vapour density (Air = 1)	: N/Av
Volatile organic Compounds (VOC's)	: N/Av
Flash point	: 58.9°C (138°F)
Flash point Method	: TCC
Lower flammable limit (% by vol.)	: N/Av
Flame Projection Length	: N/Av
Absolute pressure of container	: N/Av
General Information	: No additional information.
Solubility in water	: Insoluble.
Evaporation rate (n-Butyl acetate = 1)	: N/Av
Volatiles (% by weight)	: N/Av
Auto-ignition temperature	: N/Av
Upper flammable limit (% by vol.)	: N/Av
Flashback observed	: N/Av
Viscosity	: < 10 cSt @ 40°C (104°F)

Section 10: STABILITY AND REACTIVITY

Stability and reactivity	: Stable under the recommended storage and handling conditions prescribed.
Hazardous polymerization	: Hazardous polymerization does not occur.
Conditions to avoid	: Avoid heat and open flame. Ensure adequate ventilation, especially in confined areas.
Materials To Avoid And Incompatibility	: See Section 7 (Handling and Storage) for further details.
Hazardous decomposition products	: None known, refer to hazardous combustion products in Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs	: Eyes, skin, respiratory system, central nervous system, blood system, liver, brain and kidneys.
Routes of exposure	: <i>Inhalation:</i> YES <i>Skin Absorption:</i> YES <i>Skin & Eyes:</i> YES <i>Ingestion:</i> YES
Irritancy	: May cause mild eye irritation. May cause mild to moderate skin irritation.
Toxicological data	: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Ingredients</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Petroleum distillates	4.6 mg/L	> 5000 mg/kg	> 2000 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic	> 5.53 mg/m ³ (mist)	> 5000 mg/kg	> 2000 mg/kg
Solvent refined heavy paraffinic distillate	N/Av	> 5000 mg/kg	> 5000 mg/kg
Naphthalene	N/Av	2200 mg/kg (rat); 533 mg/kg (mouse)	> 20,000 mg/kg
Xylene	6350 ppm	3523 mg/kg	12,180 mg/kg

Carcinogenic status	: Contains Naphthalene. Naphthalene is classified as carcinogenic by IARC (Group 2B) and NTP (Group 2 - Reasonably anticipated). Contains the following chemicals listed as confirmed animal carcinogens (A3) by ACGIH: Petroleum distillates. Use caution when pouring this material. This product can generate a complex mixture of airborne material during heating or in a fire. This combustion material can include carcinogenic polycyclic aromatic hydrocarbons.
Reproductive effects	: Not expected to cause reproductive effects.
Teratogenicity	: This product contains Xylene. Xylene may cause fetotoxic effects at doses which are not maternally toxic, based on animal data.
Mutagenicity	: Not expected to be mutagenic in humans.
Epidemiology	: None known or reported by the manufacturer.
Sensitization to material	: May cause an allergic skin reaction (e.g. hives, rash) in some hypersensitive individuals. No data available to indicate product or components may be respiratory sensitizers.
Synergistic materials	: None known or reported by the manufacturer.
other important hazards	: CNS depression may result from extreme exposures.

Conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory or blood system disorders.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity : The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. This product contains the following substance which may also be hazardous for the environment: Naphthalene; Xylene.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Petroleum distillates	68476-34-6	21 mg/L (Rainbow trout)	N/Av	None.
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 5000 mg/L (Rainbow trout)	N/Av	None.
Solvent refined heavy paraffinic distillate	64741-88-4	> 5000 mg/L (Rainbow trout)	N/Av	None.
Naphthalene	91-20-3	0.11 mg/L (Rainbow trout)	0.12 mg/L	1
Xylene	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Petroleum distillates	68476-34-6	49 - 94 mg/L (Daphnia magna)	N/Av	None.
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 1000 mg/L (Daphnia magna)	N/Av	None.
Solvent refined heavy paraffinic distillate	64741-88-4	> 1000 mg/L (Daphnia magna)	N/Av	None.
Naphthalene	91-20-3	2.16 mg/L (Daphnia magna)	0.22 mg/L	None.
Xylene	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Petroleum distillates	68476-34-6	10 mg/L/72hr (Green algae)	3 mg/L (NOEL)	None.
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 1000 mg/L/96hr (Green algae)	N/Av	None.
Solvent refined heavy paraffinic distillate	64741-88-4	N/Av	N/Av	None.
Naphthalene	91-20-3	0.4 mg/L/72hr (Green algae)	N/Av	1
Xylene	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.

Mobility : No data is available on the product itself.**Persistence** : Not expected to be rapidly biodegradable.

Bioaccumulation potential : No data is available on the product itself.
 Contains: Naphthalene; Xylene. The log Kow value for Naphthalene is 3 - 3.5, and its bioconcentration factor (BCF) is 430. The log Pow for Xylene is 3.12.

Other Adverse Environmental effects

: No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle waste according to recommendations in Section 7. Do not cut, weld, drill or grind on or near this container. Empty containers retain residue (liquid and/or vapour) and can be dangerous.
- Methods of Disposal** : Dispose of in accordance with federal, provincial and local hazardous waste laws.

SECTION 14: TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN1268	PETROLEUM PRODUCTS, N.O.S.	3	III	
TDG Additional information	This material may be shipped as non-regulated material when in small means of containment (<450 Litres), provided the requirements of TDG section 1.33 are met. Section 1.33 of the Regulations is an exemption permitting the transportation of this product in small means of containment as not regulated.				

SECTION 15 - REGULATORY INFORMATION**Labelling:**

WARNING! Combustible liquid and vapour. Harmful if inhaled. Harmful or fatal if swallowed. May be harmful if absorbed through the skin. May cause respiratory irritation. May cause nausea, vomiting, headache and other central nervous system effects. May be an aspiration hazard. Can enter the lungs and cause damage. May cause skin irritation. Contains material which can cause damage to the blood system, the liver and the kidneys. Contains material which may cause cancer, based on animal data. Possible birth defect hazard - contains material that may cause birth defects, based on animal data.

PRECAUTIONS: Use in a well-ventilated area. Wear suitable protective equipment during handling. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Use proper bonding and grounding techniques when transferring liquid. Avoid contact with incompatible materials. Wash thoroughly after handling. Keep containers closed when not in use. Store in a cool, dry, well ventilated area, away from heat and ignition sources.

FIRST AID: If inhaled, move to fresh air. If breathing stopped, begin artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention. For skin contact, wash with soap and water while removing contaminated clothing. If irritation persists, seek prompt medical attention. For eye contact, flush with running water for at least 15 minutes. If irritation persists, seek prompt medical attention. If ingested, do not induce vomiting. Never give anything by mouth to an unconscious person. Seek immediate medical attention/advice.

Refer To Material Safety Data Sheet for further information.

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

SECTION 16 - OTHER INFORMATION

- Legend** :
- ACGIH: American Conference of Governmental Industrial Hygienists
 - CAS: Chemical Abstract Services
 - CNS: Central Nervous System
 - HSDB: Hazardous Substances Data Bank
 - IARC: International Agency for Research on Cancer
 - Inh: Inhalation
 - IUCLID: International Uniform Chemical Information Database
 - LC: Lethal Concentration
 - LD: Lethal Dose
 - MSHA: Mine Safety and Health Administration

N/Ap: Not Applicable
N/Av: Not Available
NIOSH: National Institute of Occupational Safety and Health
NOEC: No observable effect concentration
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PEL: Permissible exposure limit
RTECS: Registry of Toxic Effects of Chemical Substances
STEL: Short Term Exposure Limit
TCC: Tagliabue Closed Cup
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System
.

References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2014.
2. International Agency for Research on Cancer Monographs, searched 2014.
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2014 (Chempendium, HSDB and RTECS).
4. Material Safety Data Sheets from manufacturer.
5. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2014..

<u>Prepared for:</u> Radiator Specialty Co. of Canada 1711 Aimco Blvd. Mississauga, ON, Canada, L4W 1H7 Telephone: 905-625-9117 (Mon. - Fri., 8 AM - 4 PM) Please direct all enquiries to Radiator Specialty.	
<u>Prepared by:</u> ICC The Compliance Center Inc. http://www.thecompliancescenter.com	

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Radiator Specialty Co. of Canada and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Radiator Specialty Co. of Canada expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Radiator Specialty Co. of Canada.

MSDS Preparation Date (mm/dd/yyyy)

: 07/27/2007

MSDS Revision Date (mm/dd/yyyy)

: 10/31/2014

Revision No.

: 4

Revision Information

: (M)SDS sections updated:
12. ECOLOGICAL INFORMATION

END OF DOCUMENT