



## 1 Identification

- **Product identifier**
- **Trade name:** 39133 Flexible Primer Surfacers
- **Article number:** 39133
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 SEM Products Inc.  
 1685 Overview Drive  
 Rock Hill, SC 29730  
 803 207 8225
- **Information department:**  
 cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 2 H371 May cause damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS04 GHS07 GHS08

· Signal word *Danger*

## · Hazard-determining components of labeling:

Quartz (SiO<sub>2</sub>)

acetone

toluene

titanium dioxide

## · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H371 May cause damage to organs.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

## · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P308+P313 IF exposed or concerned: Get medical advice/attention.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

USA



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 2)

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 4

Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**

Health = \*1

Fire = 4

Reactivity = 3

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.\* **3 Composition/information on ingredients**· **Chemical characterization: Mixtures**· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

|            |                                       |          |
|------------|---------------------------------------|----------|
| 68476-86-8 | Petroleum gases, liquefied, sweetened | 13 - 30% |
| 67-64-1    | acetone                               | 13 - 30% |
| 14808-60-7 | Quartz (SiO <sub>2</sub> )            | 13 - 30% |
| 1330-20-7  | xylene                                | 10 - 13% |
| 110-19-0   | isobutyl acetate                      | 7 - 10%  |
| 108-88-3   | toluene                               | 1.5 - 5% |
| 123-86-4   | n-butyl acetate                       | 1.5 - 5% |
| 13463-67-7 | titanium dioxide                      | 1.5 - 5% |
| 78-93-3    | butanone                              | 1.5 - 5% |

\* **4 First-aid measures**· **Description of first aid measures**· **General information:** Immediately remove any clothing soiled by the product.· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

**Trade name:** 39133 Flexible Primer Surfacers

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

USA

(Contd. on page 5)



**Trade name: 39133 Flexible Primer Surfacers**

(Contd. of page 4)

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

### 67-64-1 acetone

|     |                                                                                                        |
|-----|--------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm                                                     |
| REL | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm                                                       |
| TLV | Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 594 mg/m <sup>3</sup> , 250 ppm |
| BEI |                                                                                                        |

### 14808-60-7 Quartz (SiO<sub>2</sub>)

|     |                                                                                       |
|-----|---------------------------------------------------------------------------------------|
| PEL | see Quartz listing                                                                    |
| REL | Long-term value: 0.05* mg/m <sup>3</sup><br>*respirable dust; See Pocket Guide App. A |
| TLV | Long-term value: 0.025* mg/m <sup>3</sup><br>*as respirable fraction                  |

### 1330-20-7 xylene

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm                                                      |
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm |
| BEI |                                                                                                       |

### 110-19-0 isobutyl acetate

|     |                                                                                                      |
|-----|------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 700 mg/m <sup>3</sup> , 150 ppm                                                     |
| REL | Long-term value: 700 mg/m <sup>3</sup> , 150 ppm                                                     |
| TLV | Short-term value: 172 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 238 mg/m <sup>3</sup> , 50 ppm |

### 108-88-3 toluene

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 200 ppm<br>Ceiling limit value: 300; 500* ppm<br>*10-min peak per 8-hr shift         |
| REL | Short-term value: 560 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 375 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 75 mg/m <sup>3</sup> , 20 ppm                                                        |
| BEI |                                                                                                       |

### 123-86-4 n-butyl acetate

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 710 mg/m <sup>3</sup> , 150 ppm                                                      |
| REL | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 710 mg/m <sup>3</sup> , 150 ppm |

(Contd. on page 6)


**Trade name: 39133 Flexible Primer Surfacer**

(Contd. of page 5)

|                                                    |                                                                                                                                                                                                                                                                                               |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TLV                                                | Short-term value: 712 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 238 mg/m <sup>3</sup> , 50 ppm                                                                                                                                                                                          |
| <b>78-93-3 butanone</b>                            |                                                                                                                                                                                                                                                                                               |
| PEL                                                | Long-term value: 590 mg/m <sup>3</sup> , 200 ppm                                                                                                                                                                                                                                              |
| REL                                                | Short-term value: 885 mg/m <sup>3</sup> , 300 ppm<br>Long-term value: 590 mg/m <sup>3</sup> , 200 ppm                                                                                                                                                                                         |
| TLV                                                | Short-term value: 885 mg/m <sup>3</sup> , 300 ppm<br>Long-term value: 590 mg/m <sup>3</sup> , 200 ppm<br>BEI                                                                                                                                                                                  |
| · <b>Ingredients with biological limit values:</b> |                                                                                                                                                                                                                                                                                               |
| <b>67-64-1 acetone</b>                             |                                                                                                                                                                                                                                                                                               |
| BEI                                                | 50 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Acetone (nonspecific)                                                                                                                                                                                                            |
| <b>1330-20-7 xylene</b>                            |                                                                                                                                                                                                                                                                                               |
| BEI                                                | 1.5 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Methylhippuric acids                                                                                                                                                                                                  |
| <b>108-88-3 toluene</b>                            |                                                                                                                                                                                                                                                                                               |
| BEI                                                | 0.02 mg/L<br>Medium: blood<br>Time: prior to last shift of workweek<br>Parameter: Toluene<br><br>0.03 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Toluene<br><br>0.3 mg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: o-Cresol with hydrolysis (background) |
| <b>78-93-3 butanone</b>                            |                                                                                                                                                                                                                                                                                               |
| BEI                                                | 2 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: MEK                                                                                                                                                                                                                               |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

(Contd. on page 7)

**Trade name: 39133 Flexible Primer Surfacers**

(Contd. of page 6)

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

|                 |                                    |
|-----------------|------------------------------------|
| Form:           | Aerosol                            |
| Color:          | According to product specification |
| Odor:           | Characteristic                     |
| Odor threshold: | Not determined.                    |

· **pH-value:** Not determined.

· **Change in condition**

|                              |               |
|------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 55 °C         |

· **Flash point:** -103 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 405 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

(Contd. on page 8)


**Trade name: 39133 Flexible Primer Surfacers**

(Contd. of page 7)

|                                                   |                                                          |
|---------------------------------------------------|----------------------------------------------------------|
| · <b>Danger of explosion:</b>                     | In use, may form flammable/explosive vapour-air mixture. |
| · <b>Explosion limits:</b>                        |                                                          |
| Lower:                                            | 1.1 Vol %                                                |
| Upper:                                            | 13.0 Vol %                                               |
| · <b>Vapor pressure at 20 °C:</b>                 | 233 hPa                                                  |
| · <b>Density at 20 °C:</b>                        | 0.81629 g/cm <sup>3</sup>                                |
| · <b>Relative density</b>                         | Not determined.                                          |
| · <b>Vapor density</b>                            | Not determined.                                          |
| · <b>Evaporation rate</b>                         | Not applicable.                                          |
| · <b>Solubility in / Miscibility with Water:</b>  | Not miscible or difficult to mix.                        |
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined.                                          |
| · <b>Viscosity:</b>                               |                                                          |
| Dynamic:                                          | Not determined.                                          |
| Kinematic:                                        | Not determined.                                          |
| · <b>Solvent content:</b>                         |                                                          |
| Organic solvents:                                 | 77.4 %                                                   |
| VOC content:                                      | 57.4 %                                                   |
|                                                   | 590.6 g/l / 4.93 lb/gal                                  |
| Solids content:                                   | 22.6 %                                                   |
| · <b>Other information</b>                        | No further relevant information available.               |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

### · LD/LC50 values that are relevant for classification:

#### 1330-20-7 xylene

|        |      |                     |
|--------|------|---------------------|
| Oral   | LD50 | 4300 mg/kg (rat)    |
| Dermal | LD50 | 2000 mg/kg (rabbit) |

#### 108-88-3 toluene

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 5000 mg/kg (rat)     |
| Dermal | LD50 | 12124 mg/kg (rabbit) |

(Contd. on page 9)



**Trade name: 39133 Flexible Primer Surfacers**

(Contd. of page 8)

Inhalative LC50/4 h 5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

|            |                                      |    |
|------------|--------------------------------------|----|
| 14808-60-7 | Quartz (SiO <sub>2</sub> )           | 1  |
| 1330-20-7  | xylene                               | 3  |
| 108-88-3   | toluene                              | 3  |
| 13463-67-7 | titanium dioxide                     | 2B |
| 14807-96-6 | Talc                                 | 3  |
| 7631-86-9  | silicon dioxide, chemically prepared | 3  |
| 1333-86-4  | Carbon black                         | 2B |
| 111-76-2   | 2-butoxyethanol                      | 3  |
| 100-41-4   | ethylbenzene                         | 2B |

· **NTP (National Toxicology Program)**

|            |                            |   |
|------------|----------------------------|---|
| 14808-60-7 | Quartz (SiO <sub>2</sub> ) | K |
|------------|----------------------------|---|

· **OSHA-Ca (Occupational Safety & Health Administration)**

|            |                             |  |
|------------|-----------------------------|--|
| 68911-87-5 | montmorilontie clay complex |  |
|------------|-----------------------------|--|

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 10)

**Trade name:** 39133 Flexible Primer Surfacers

(Contd. of page 9)

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **Transport hazard class(es)**

- **DOT**



- **Class** 2.1
- **Label** 2.1

- **ADR**



- **Class** 2 5F Gases
- **Label** 2.1

- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

- **Packing group**

- **DOT, ADR, IMDG, IATA** Void

- **Environmental hazards:**

- **Marine pollutant:** No

- **Special precautions for user** Warning: Gases

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS



Printing date 05/23/2016

Reviewed on 05/17/2016

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 10)

|                                                                                  |                                                                                                                                                                                                                                                                                                                                      |
|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| · <b>EMS Number:</b>                                                             | F-D,S-U                                                                                                                                                                                                                                                                                                                              |
| · <b>Stowage Code</b>                                                            | SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre:<br>Category A. For AEROSOLS with a capacity above 1 litre:<br>Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.                                                                                                     |
| · <b>Segregation Code</b>                                                        | SG69 For AEROSOLS with a maximum capacity of 1 litre:<br>Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre:<br>Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.                                                                                                                                                                                                                                                                                                                      |
| · <b>Transport/Additional information:</b>                                       |                                                                                                                                                                                                                                                                                                                                      |
| · <b>DOT</b>                                                                     |                                                                                                                                                                                                                                                                                                                                      |
| · <b>Quantity limitations</b>                                                    | On passenger aircraft/rail: 75 kg<br>On cargo aircraft only: 150 kg                                                                                                                                                                                                                                                                  |
| · <b>ADR</b>                                                                     |                                                                                                                                                                                                                                                                                                                                      |
| · <b>Excepted quantities (EQ)</b>                                                | Code: E0<br>Not permitted as Excepted Quantity                                                                                                                                                                                                                                                                                       |
| · <b>IMDG</b>                                                                    |                                                                                                                                                                                                                                                                                                                                      |
| · <b>Limited quantities (LQ)</b>                                                 | 1L                                                                                                                                                                                                                                                                                                                                   |
| · <b>Excepted quantities (EQ)</b>                                                | Code: E0<br>Not permitted as Excepted Quantity                                                                                                                                                                                                                                                                                       |
| · <b>UN "Model Regulation":</b>                                                  | UN 1950 AEROSOLS, 2.1                                                                                                                                                                                                                                                                                                                |

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

### · Section 313 (Specific toxic chemical listings):

|            |                 |
|------------|-----------------|
| 1330-20-7  | xylene          |
|            | ACRYLIC RESIN   |
| 108-88-3   | toluene         |
| 78-93-3    | butanone        |
| 14807-96-6 | Talc            |
| 111-76-2   | 2-butoxyethanol |
| 100-41-4   | ethylbenzene    |
| 67-56-1    | methanol        |

### · TSCA (Toxic Substances Control Act):

|         |         |
|---------|---------|
| 67-64-1 | acetone |
|---------|---------|

(Contd. on page 12)

USA



Printing date 05/23/2016

Reviewed on 05/17/2016

**Trade name: 39133 Flexible Primer Surfacers**

(Contd. of page 11)

|            |                                                                |
|------------|----------------------------------------------------------------|
| 14808-60-7 | Quartz (SiO <sub>2</sub> )                                     |
| 1330-20-7  | xylene                                                         |
| 110-19-0   | isobutyl acetate                                               |
| 108-88-3   | toluene                                                        |
| 123-86-4   | n-butyl acetate                                                |
| 13463-67-7 | titanium dioxide                                               |
| 78-93-3    | butanone                                                       |
| 14807-96-6 | Talc                                                           |
| 68911-87-5 | montmorillonite clay complex                                   |
| 16883-83-3 | benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate |
| 7631-86-9  | silicon dioxide, chemically prepared                           |
| 21645-51-2 | aluminium hydroxide                                            |
| 51274-00-1 | YELLOW IRON OXIDE                                              |
| 1333-86-4  | Carbon black                                                   |

· **Proposition 65**

· **Chemicals known to cause cancer:**

|            |                            |
|------------|----------------------------|
| 14808-60-7 | Quartz (SiO <sub>2</sub> ) |
| 1330-20-7  | xylene                     |
| 13463-67-7 | titanium dioxide           |
| 1333-86-4  | Carbon black               |
| 100-41-4   | ethylbenzene               |

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

|          |          |
|----------|----------|
| 108-88-3 | toluene  |
| 67-56-1  | methanol |

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

|           |                 |    |
|-----------|-----------------|----|
| 67-64-1   | acetone         | I  |
| 1330-20-7 | xylene          | I  |
| 108-88-3  | toluene         | II |
| 78-93-3   | butanone        | I  |
| 111-76-2  | 2-butoxyethanol | NL |
| 100-41-4  | ethylbenzene    | D  |

· **TLV (Threshold Limit Value established by ACGIH)**

|            |                            |    |
|------------|----------------------------|----|
| 67-64-1    | acetone                    | A4 |
| 14808-60-7 | Quartz (SiO <sub>2</sub> ) | A2 |
| 1330-20-7  | xylene                     | A4 |
| 108-88-3   | toluene                    | A4 |

(Contd. on page 13)

**Trade name: 39133 Flexible Primer Surfacers**

(Contd. of page 12)

|            |                  |    |
|------------|------------------|----|
| 13463-67-7 | titanium dioxide | A4 |
| 14807-96-6 | Talc             | A4 |
| 1333-86-4  | Carbon black     | A4 |
| 111-76-2   | 2-butoxyethanol  | A3 |
| 100-41-4   | ethylbenzene     | A3 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

|            |                            |
|------------|----------------------------|
| 14808-60-7 | Quartz (SiO <sub>2</sub> ) |
| 13463-67-7 | titanium dioxide           |
| 1333-86-4  | Carbon black               |
| 67-56-1    | methanol                   |

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Quartz (SiO<sub>2</sub>)  
acetone  
toluene  
titanium dioxide

· **Hazard statements**

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H350 May cause cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H371 May cause damage to organs.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P211 Do not spray on an open flame or other ignition source.  
P280 Wear protective gloves.  
P280 Wear eye protection / face protection.  
P264 Wash thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 Specific treatment (see on this label).  
P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 14)

**Trade name: 39133 Flexible Primer Surfacers**

(Contd. of page 13)

P332+P313      *If skin irritation occurs: Get medical advice/attention.*  
 P337+P313      *If eye irritation persists: Get medical advice/attention.*  
 P314              *Get medical advice/attention if you feel unwell.*  
 P302+P352      *IF ON SKIN: Wash with plenty of water.*  
 P362+P364      *Take off contaminated clothing and wash it before reuse.*  
 P405              *Store locked up.*  
 P410+P403      *Protect from sunlight. Store in a well-ventilated place.*  
 P410+P412      *Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*  
 P501              *Dispose of contents/container in accordance with local/regional/national/international regulations.*

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**  
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**  
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.  
Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environment protection department.
- **Contact:** Steve Gaver (sgaver@semproducts.com)
- **Date of preparation / last revision** 05/23/2016 / 8
- **Abbreviations and acronyms:**  
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flam. Aerosol 1: Aerosols – Category 1  
 Press. Gas: Gases under pressure – Compressed gas  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
 Carc. 1A: Carcinogenicity – Category 1A  
 Repr. 2: Reproductive toxicity – Category 2

(Contd. on page 15)



Printing date 05/23/2016

Reviewed on 05/17/2016

**Trade name: 39133 Flexible Primer Surfacer**

STOT SE 2: Specific target organ toxicity (single exposure) – Category 2  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. of page 14)

· **\* Data compared to the previous version altered.**

USA